Oasis 60 x 32 ABF Configured, Simulated Tile Wall Bathtub With ActivLife 3-Bar (2-horizontal, 1-vertical) Package




Specification – Oasis one-piece, 60 x 32-inch deep, FRP gelcoat flat wall bathtub model TST-6032 offered in a standard 16-inch or 17.25-inch (ABF) apron height. ActivLife package includes a single horizontal bar on the back wall and control wall, and a vertical bar at the entry on the control wall.

Standards Certification:

The bathtub listed is manufactured in compliance with ANSI Z124 Standards, and certified through an ongoing, independent quality assurance and testing program.

The factory-applied grab bar package is certified through an independent review program.



Model ID	Package Code	Description (define configuration referencing drain end)
TST-6032 L (Std or ABF) TST-6032 R (Std or ABF)	/ BP2-60 (left drain) / BP2-60 (right drain)	60" x 32", end drain, tub-shower with 16" (Std) or 17.25" (ABF) apron, and ActivLife 1.50" dia. stainless steel 3-bar package (single horizontal bars on back wall and control wall, single vertical bar on control wall).
Powder Coated Bar Packages (1.25-inch dia.)		
TST-6032 L (Std or ABF) TST-6032 R (Std or ABF)	/ BP2-60 WHT (left drain) / BP2-60 WHT (right drain)	60" x 32", end drain, tub-shower with 16" (Std) or 17.25" (ABF) apron, and ActivLife 1.25" dia. white powder coated, 3-bar package (single horizontal bars on back wall and control wall, single vertical bar on control wall).
TST-6032 L (Std or ABF) TST-6032 R (Std or ABF)	/ BP2-60 SNK (left drain) / BP2-60 SNK (right drain)	60" x 32", end drain, tub-shower with 16" (Std) or 17.25" (ABF) apron, and ActivLife 1.25" dia. nickel 3-bar package (single horizontal bars on back wall and control wall, single vertical bar on control wall).

ADD / SHWR ROD-TS Factory installed 1" dia. stainless steel shower curtain rod.








Photo 1: Grab Bars: Factory-installed 1.50-inch diameter, concealed attachment, 18 gauge, #304 brushed stainless steel grab bars. Concealed attachment design provides tamper-resistance and minimizes debris collection areas at contact points, compared to common exposed flange bar designs, without compromising bar attachment integrity. (Reinforced areas include a structural core material encapsulated in FRP composite.)

Photo 2: Grab Bars: Factory-installed 1.25-inch dia. powder coated (in finishes listed above), concealed attachment, 18 gauge, #304 stainless steel grab bars. Concealed attachment design provides tamper-resistance and minimizes debris collection areas at contact points, compared to common exposed flange bar designs, without compromising bar attachment integrity. (Reinforced areas include a structural core material encapsulated in FRP composite.)

Available Factory Installed Packages (model available without any component or reinforcement packages) Component Packages:

ANS17 package code:
 ADA10 package code:
 5-bar package with folding or removable RH or LH seat & shower rod, based on ANSI-2017
 4-bar package with folding or removable RH or LH seat & shower rod, based on ADA-2010
 5BAR package code:
 4-bar package replicates ANS17 bar configuration (less seat & shower rod)
 4-bar package replicates ADA10 bar configuration (less seat & shower rod)

5. BP1-60 & BP2-60 package codes: 2-wall, 2-bar or 3-bar packages

Reinforced ONLY Packages:

- 6. FH package code: reinforcement for a single vertical & horizontal bars, based on HUD/FHA-Fair Housing
- 7. 3SM & 3SF package codes: expanded reinforcement packages, (with or without package components)