Oasis 60 x 32 ABF Configured, Simulated Tile Wall Bathtub With (2010 ADA Standards) 4-Horizontal Bars And REMOVABLE Seat Package



Specification - Oasis one-piece, 60 x 32-inch deep, FRP gelcoat flat wall bathtub model TST-6032 ABF (17.25-inch apron) having a factory-equipped package in compliance with 2010 ADA Standards for Accessible Design. Package includes 2-horizontal bars on back wall, single horizontal bar on head end wall, horizontal bar on control wall, REMOVABLE in-tub seat at head end and shower curtain rod.

Standards Certification:

The bathtub listed is manufactured in compliance with ANSI Z124 Standards, and certified through an ongoing, independent quality assurance and testing program.

The factory-applied grab bars and seat package are installed in compliance with 2010 ADA Standards for Accessible Design, and certified through an independent review program.




TST-6032 L ABF / ADA10-REM

(LH drain / 17.25" apron) Model & Package Illustrated







Dimensions shown are maximum. Due to the nature of the materials involved, actual unit dimensions can vary (tolerances: +0 / -1/8 inch). Oasis reserves the right to modify or discontinue product and/or associated equipment without prior written or verbal notification or obligation

Model ID	Package Code	Description (define configuration referencing drain end)
TST-6032 L ABF TST-6032 R ABF	/ ADA10-REM / ADA10-REM	60" x 32", end drain, flat wall tub-shower, with 17.25" apron, 4-bars (dual horizontal back wall bars, single horizontal bar on head end wall and control wall) with white articulated removable seat and shower curtain rod.
	DELETE / SHWR ROD-TS	Delete shower curtain rod from package. (DOES NOT compromise compliance).
Option:	CRT-TS	Site installed white 150 denier fabric bottom weighted shower curtain with integrated rings












Photo 1: Grab Bars: Factory-installed 1.50-inch diameter, concealed attachment, 18 gauge, #304 brushed stainless steel grab bars. Concealed attachment design provides tamper-resistance and minimizes debris collection areas at contact points, compared to common exposed flange bar designs, without compromising bar attachment integrity. (Reinforced areas include a structural core material encapsulated in FRP composite.)

- Photo 2: REMOVABLE In-Tub Seat: Factory-installed stainless steel (back wall) bracket provides stabile and secure locking for removable slatted bench seat. The individual seat slats are a molded, non-porous plastic linked together by a slat-to-slat hinge mechanism. The seat articulates for east insertion and removal from bracket and folds for convenient storage. (Bracket reinforced area is a structural core material encapsulated in FRP composite.)
- Photo 3: Shower Curtain Rod: Factory-installed 1.00-inch diameter, concealed attachment, 18 gauge, stainless steel shower curtain rod with polished finished.
- Photo 4: Shower Curtain: White, 150 denier fabric, bottom weighted shower curtain with integrated rings.

Available Factory Installed Packages (model available without any component or reinforcement packages)

Component Packages:

1 ANS17 package code: 5-bar package with folding or removable RH or LH seat & shower rod, based on ANSI-2017
2. ADA10 package code: 4-bar package with folding or removable RH or LH seat & shower rod, based on ADA-2010

5-bar package replicates ANS17 bar configuration (less seat & shower rod)
 4BAR package code:
 4-bar package replicates ADA10 bar configuration (less seat & shower rod)

5. BP1-60 & BP2-60 package codes: 2-wall, 2-bar or 3-bar packages

Reinforced ONLY Packages:

- 6. FH package code: reinforcement for a single vertical & horizontal bars, based on HUD/FHA-Fair Housing
- 7. 3SM & 3SF package codes: expanded reinforcement packages, (with or without package components)